

SALW Guide

Global distribution and visual
identification


























Ecuador

Country report

<https://salw-guide.bicc.de>

Weapons Distribution

The following list shows the weapons which can be found in *Ecuador* and whether there is data on who holds these weapons:

AR 15 (M16/M4)		HK MP5	
Browning M 2		IGLA (SA-16 / SA-18)	
Colt M1911		M203 grenade launcher	
Daewoo K1 / K2		Mauser K98	
FN FAL		MG 3 / MG 42	
FN Herstal FN MAG		Mossberg 500	
FN High Power		MP UZI	
GDATP MK 19		Remington 870P	
Glock 17		SIG SG540	
HK 21		Steyr AUG	
HK 23		Strela (SA-7 / SA-14)	
HK33			

Explanation of symbols



Country of origin



Licensed production



Production without a licence



Government: Sources indicate that this type of weapon is held by Governmental agencies.



Non-Government: Sources indicate that this type of weapon is held by non-Governmental armed groups.



Unspecified: Sources indicate that this type of weapon is found in the country, but do not specify whether it is held by Governmental agencies or non-Governmental armed groups.

It is entirely possible to have a combination of tags beside each country. For example, if country X is tagged with a G and a U, it means that at least one source of data identifies Governmental agencies as holders of weapon type Y, and at least one other source confirms the presence of the weapon in country X without specifying who holds it.

Note: This application is a living, non-comprehensive database, relying to a great extent on active contributions (provision and/or validation of data and information) by either SALW experts from the military and international renowned think tanks or by national and regional focal points of small arms control entities.

AR 15 (M16/M4)

The heart of the AR-15 is the direct gas system. This system uses no conventional gas piston and rod to propel bolt group back after the shot is fired. Instead, the hot powder gases are fed from the barrel and down to the stainless steel tube into the receiver. Inside the receiver, the rear end of the gas tube enters into the "gas key", a small attachment on the top of the bolt carrier. The hot gases, through the gas key, enter the hollow cavity inside the bolt carrier and expands there, acting against the bolt carrier and the collar around the bolt body. The pressure of the gases causes the bolt carrier to move back against initially stationary bolt. At least 8 million items were produced. The CQ is a variant of the AR-15 rifle manufactured by the Chinese arms company, NORINCO. The "Terab" rifle is a clone of the Norinco CQ manufactured by the MIC (Military Industry Corporation) of Sudan. The "Armada" rifle is a clone of the Norinco CQ manufactured by S.A.M. - Shooter's Arms Manufacturing, a.k.a. Shooter's Arms Guns & Ammo Corporation, in the Philippines. The CQ/Terab has been observed in South Sudan used by some rebel groups in 2013.



Category	<i>Assault Rifles</i>
Operating system	Gas operated, rotating bolt
Cartridge	5.56 x 45mm / .223 Remington
Length	986 mm
Feeding	Box magazine

The following ammunition can be used by the **AR 15 (M16/M4)**:

5.56 x 45mm / .223 Remington

Bullet diameter	5.7 mm
Case length	44.7 mm
Overall length	57.4 mm



Browning M 2

The Browning .50 caliber machine gun has been used extensively as a vehicle weapon and for aircraft armament. The M2 fires from a closed bolt, operated on the short recoil principle. Nearly 5 million items were produced.



Category	<i>Heavy Machine Guns</i>
Operating system	Fires from a short bolt, operated on the short recoil principle
Cartridge	12.7 x 99 mm NATO (.50BMG)
Length	1650 mm
Feeding	Belt

The following ammunition can be used by the **Browning M 2**:

12.7 x 99 mm NATO (.50BMG)

Bullet diameter	13 mm
Case length	99 mm
Overall length	138 mm



Colt M1911

Technically, the M1911 is a recoil operated, locked breech semi-auto pistol. It has a single action trigger with frame mounted safety that locks the hammer and the slide. The hammer can be locked either in cocked or in lowered position, allowing the gun to be carried in "cocked and locked" state, with safety on, hammer cocked and round chambered. Additional automated safety is incorporated into the rear of the grip and locks the action, when the gun is not properly held. The Colt M 1911 was manufactured by many companies in many countries, partly in the original form, partly modified, partly under license and partly without a license. It was exported to many countries after WW II, and it was in service with the US forces for 70 years.




Category	<i>Self-Loading Pistols & Revolvers</i>
Operating system	Short recoil operated, closed breech, single action, semi-automatic

Cartridge	.45 ACP
Length	219 mm
Feeding	Box magazine

The following ammunition can be used by the **Colt M1911**:

.45 ACP

Bullet diameter	11.5 mm
Case length	22.8 mm
Overall length	32 mm



Daewoo K1 / K2

The South Korean Daewoo K1A was developed as a short-barrelled version of the K2 assault rifle explaining their technical and physical resemblance. The K1A is the enhanced version of the previous mass produced K1 rifle. Furthermore, the rifles combine technical elements of the operating systems from the AR15/M16-rifles and the AK-series. Both the K1 and K2 are still in production and in service within the South Korean Armed Forces. *length depends on the model: - Daewoo K1A: 838 mm stock extended - Daewoo K2: 980 mm butt extended*



Category	<i>Assault Rifles</i>
Operating system	gas piston, selective fire with 3rd burst
Cartridge	5.56 x 45mm / .223 Remington
Length	838 mm
Feeding	detachable, box magazine

The following ammunition can be used by the **Daewoo K1 / K2**:

5.56 x 45mm / .223 Remington

Bullet diameter	5.7 mm
-----------------	--------

Case length	44.7 mm
Overall length	57.4 mm



FN FAL

The FN FAL (Fusil Automatique Leger - Light Automatic Rifle) is one of the most famous and widespread military rifle designs of the 20th century. It can be found in both the 7.62 NATO and, very rarely, the 5.56 NATO versions. The furniture may be wood, metal or plastic. There are various barrel lengths. In the UK (L1A1), Canadian, Indian and Dutch versions, there is no automatic fire mode. The gas system is fitted with a gas regulator, so that it could be easily adjusted for various environment conditions, or cut off completely, so that rifle grenades could be safely launched from the barrel.



Category	<i>Assault Rifles</i>
Operating system	Gas operated, tilting breechblock, select-fire or semi-automatic only
Cartridge	7.62 x 51mm / .308 Winchester
Length	1100 mm
Feeding	Box magazine

The following ammunition can be used by the **FN FAL**:

7.62 x 51mm / .308 Winchester

Bullet diameter	7.82 mm
Case length	51.18 mm
Overall length	69.85 mm



FN Herstal FN MAG

The Belgian FN MAG (Mitrailleuse d'Appui Général, meaning general-purpose machine gun) entered into production in 1958. It is one of the most widespread machine gun designs and is used in more than 90 countries around the globe. It is still manufactured in Belgium and produced under license in several countries including Argentina, Egypt, the US and the UK. It can be carried by infantry and is usually fired while mounted on a tripod.



Category	<i>Heavy Machine Guns</i>
Operating system	gas, automatic
Cartridge	7.62 x 51mm / .308 Winchester
Length	1260 mm
Feeding	disintegrating metal link belt

The following ammunition can be used by the **FN Herstal FN MAG**:

7.62 x 51mm / .308 Winchester

Bullet diameter	7.82 mm
Case length	51.18 mm
Overall length	69.85 mm



FN High Power

The High Power is one of the most widely used military pistols of all time, having been used by the armed forces of over 50 countries. The pistol is often referred to as an HP (for "Hi Power" or "High Power") or as a GP (for the French term, "Grande Puissance"). Technically, the High Power pistol, also known as Browning HP 35, GP 35 or Model 1935, is a recoil operated, locked breech pistol. It uses linkless barrel to slide locking invented by Browning. The trigger is single action, with external hammer. Original HPs featured frame mounted safety at the left side of the frame, that locks both sear and slide. Modern versions, since Mark II, also featured ambidextrous safety levers, that are also more comfortable to operate.



Category	<i>Self-Loading Pistols & Revolvers</i>
-----------------	---

Operating system	Short recoil operated, locked breech, single action
Cartridge	.40 S&W 9mm Parabellum (9 x 19mm)
Length	200 mm
Feeding	Box magazine

The following ammunition can be used by the **FN High Power**:

.40 S&W

Bullet diameter	10.2 mm
Case length	21.6 mm
Overall length	28.8 mm



9mm Parabellum (9 x 19mm)


Bullet diameter	9 mm
Case length	19.15 mm
Overall length	29.69 mm



GDATP MK 19

The MK 19 or Mark 19 grenade machine gun was designed in the 1960s for the US Navy in the Vietnam War. In the following decades, the MK 19 was further improved, sold to and adopted by at least 28 other nations including Australia, Chile and South Korea. It was originally designed to be mounted on (naval) vehicles, but current systems can also be ground- or turret-mounted. The MK 19 can be fired manually or even remotely.

Original manufacturer General Dynamics Armament and Technical Products (GDATP).



Category	<i>Hand-held under-barrel and Mounted Grenade Launchers</i>
Operating system	blowback, open-bolt (advanced primer ignition in mods 1 and 2)
Cartridge	40x53 mm
Length	1095 mm

Feeding	linked belt with 32 or 48 rds
----------------	-------------------------------

The following ammunition can be used by the **GDATP MK 19**:

40x53 mm

Bullet diameter	40 mm
Case length	53 mm
Overall length	-



Glock 17

Several modified versions of the Glock 17 have also been introduced. The Glock 17C incorporated slots cut in the barrel and slide to compensate for muzzle rise and recoil. The Glock 17L incorporates a longer slide and extended barrel. Initially, the Glock 17L had three holes in the top of the barrel and a corresponding slot in the slide; however, later production pistols lack the holes in the barrel. The Glock 17MB is a version with ambidextrous magazine catch. Glock pistols are designed with three independent safety mechanisms to prevent accidental discharge. The system, designated "Safe Action" by Glock, consists of an external integrated trigger safety and two automatic internal safeties: a firing pin safety and a drop safety. The external safety is a small inner lever contained in the trigger.



Category	<i>Self-Loading Pistols & Revolvers</i>
Operating system	short recoil-operated, locked breech
Cartridge	9mm Parabellum (9 x 19mm)
Length	186 mm
Feeding	Box magazine

The following ammunition can be used by the **Glock 17**:

9mm Parabellum (9 x 19mm)

Bullet diameter	9 mm
Case length	19.15 mm

Overall length	29.69 mm
----------------	----------



HK 21

The basic action of the machine gun, which received the company designation HK 21, was similar to that of the G3 rifle. The HK 21 fired from a closed bolt (not that big issue since its heavy barrel was really quick-detachable) and, unlike most machine guns, its belt feeding module was located below the receiver. Variants: HK11E automatic rifle (magazine fed, 7.62 mm) HK13E automatic rifle (magazine fed, 5.56 mm) HK21E general purpose machine gun (belt feed, 7.62 mm) HK23E light machine gun (belt-fed, 5.56 mm). The "E" stands for "Export" model.



Category	<i>Light Machine Guns</i>
Operating system	Selective fire roller-back blowback
Cartridge	7.62 x 51mm / .308 Winchester
Length	1140 mm
Feeding	Box magazine

The following ammunition can be used by the **HK 21**:

7.62 x 51mm / .308 Winchester

Bullet diameter	7.82 mm
Case length	51.18 mm
Overall length	69.85 mm



HK 23

The HK (Heckler & Koch) 23 emerged in 1972 from the original HK 21, which explains the optical and technical resemblance between them and their variants. Usually it is fired from a bipod, but it can also be tripod mounted. While the production of the original HK 21 and 23 have officially ceased, there are still models in production. Residual numbers may remain in service. An “E” added to the weapon’s name identifies models for export.



Category	<i>Light Machine Guns</i>
Operating system	Selective fire roller-back blowback
Cartridge	5.56 x 45mm / .223 Remington
Length	1030 mm
Feeding	Box magazine

The following ammunition can be used by the **HK 23**:

5.56 x 45mm / .223 Remington

Bullet diameter	5.7 mm
Case length	44.7 mm
Overall length	57.4 mm



HK33

The Heckler & Koch HK33 entered into production in 1963. The HK33 is produced in five variants: 1) with a fixed butt; 2) with a retractable butt; 3) fitted with a bipod; 4) as a sniper rifle with telescopic sight; and 5) as the HK22K carbine version. An “E” added to the weapon’s name identifies models for export, while a “K” added to the end of the weapon’s name refers to shortened models.



Category	<i>Assault Rifles</i>
Operating system	delayed-blowback, selective-fire

Cartridge	5.56 x 45mm / .223 Remington
Length	920 mm
Feeding	detachable box magazine

The following ammunition can be used by the **HK33**:

5.56 x 45mm / .223 Remington

Bullet diameter	5.7 mm
Case length	44.7 mm
Overall length	57.4 mm



HK MP5

Though the Heckler & Koch MP5 was designed in the 1960s, it is still one of the most widely deployed sub-machine guns and has been developed into a family with numerous variants. The gun features either a fixed or a sliding (telescoping) butt-stock. The original MP5 offers a choice of single shot or automatic fire, whereas later models received a burst-fire device, allowing two or three-round-bursts each time the trigger is operated. Current models remain in (licensed) production in several countries, though The China North Industries Corporation, officially abbreviated as Norinco, manufactures an unlicensed copy, the NR08.



Category	<i>Submachine Guns</i>
Operating system	delayed-blowback; selective-fire
Cartridge	9mm Parabellum (9 x 19mm)
Length	680 mm
Feeding	detachable box magazine

The following ammunition can be used by the **HK MP5**:

9mm Parabellum (9 x 19mm)

Bullet diameter	9 mm
Case length	19.15 mm
Overall length	29.69 mm



IGLA (SA-16 / SA-18)

The main differences between the SA-18, the SA-16 and its predecessor Strela-3 (SA-14) included an optional "Identification Friend or Foe"-system to prevent firing on friendly aircraft, an automatic lead and super elevation to simplify shooting and reduce minimum firing range, a slightly larger rocket, reduced drag and better guidance system extend maximum range and improve performance against fast and maneuverable targets, an improved lethality on target achieved by a combination of delayed impact fusing, terminal maneuver to hit the fuselage rather than jet nozzle, an additional charge to set off the remaining rocket fuel (if any) on impact, an improved resistance to infrared countermeasure, and slightly improved seeker sensitivity. Several guerrilla and terrorist organizations are also known to have Iglas.



Category	<i>Portable Launcher of Anti-aircraft Missile Systems</i>
Operating system	MANPAD
Cartridge	
Feeding	front-loaded

The following ammunition can be used by the **IGLA (SA-16 / SA-18)**:

M203 grenade launcher

The M203 grenade launcher was intended to be used as close fire support for point and group area targets. The round is designed to be effective at penetrating windows, blowing up doors, producing casualties in groups of enemies, destroying bunkers, and damaging or disabling soft-skinned vehicles. Its primary purpose is to engage enemies in dead space that cannot be reached by direct fire. A well-trained M203 gunner can also use his weapon to suppress the enemy, both from movement and sight. M203 were also produced in Egypt, South Korea and Bulgaria (as UBGL-M1, with mount suitable for Kalashnikov AKM and AK-74 type rifles).



Category	<i>Hand-held under-barrel and Mounted Grenade Launchers</i>
Operating system	Single shot, under-barrel, pump-action
Cartridge	40 x 46 mm grenade
Length	380 mm
Feeding	breech-loaded

The following ammunition can be used by the **M203 grenade launcher**:

40 x 46 mm grenade

Bullet diameter	-
Case length	-
Overall length	-



Mauser K98

There are many variants of this weapon, and it has been widely copied. A number of non-European nations used the Mauser Karabiner 98k rifle as well as a few guerrilla organizations to help establish new nation-states. One example was Israel who used the Mauser Karabiner 98k rifle from the late 1940s until the 1970s. During the 1990s, the Yugoslavian Karabiner 98k rifles and the Yugoslavian M48 and M48A rifles were used alongside modern automatic and semi-automatic rifles by all the warring factions of the Yugoslav wars. There are a number of photographs taken during the war in Bosnia showing combatants and snipers using Yugoslavian-made Mauser rifles from high-rise buildings in the Bosnian city of Sarajevo.



Category	<i>Rifles & Carbines</i>
Operating system	Manually operated, rotating bolt
Cartridge	7.92x57 mm (8x57 IS)
Length	1110 mm
Feeding	Internal magazine

The following ammunition can be used by the **Mauser K98**:

7.92x57 mm (8x57 IS)

Bullet diameter	8.08 mm
Case length	57 mm
Overall length	82 mm



MG 3 / MG 42

The MG is a short-recoil operated, air cooled, belt fed weapon which fires from an open bolt. The barrel is quick-removable, and can be replaced in less than six seconds by a properly trained crew. The action of the weapon is operated by the recoil of the locked barrel, assisted by a muzzle booster which uses pressure from the muzzle blast to increase the recoil impulse. This is a simple and solid system. Variants: MG 1: Rheinmetall variant of the MG 42, most notably rechambered to fire 7.62×51mm NATO. MG 1A1 (MG 42/58): As MG 1, but with sights properly calibrated for the new round. Sights refitted to existing MG 1s. MG 1A2 (MG 42/59): MG 1A1 variant; product improved with longer ejection port, heavy bolt and friction ring buffer. MG 1A3: MG 1A2 variant; product improvement of all major components. MG 1A4: MG 1 variant; for fixed mount armor use. MG 1A5: MG 1A3 variant; MG1A3s converted to MG1A4 standard. MG 2: Designation for all wartime MG 42s rechambered to 7.62×51mm NATO. MG 3: MG 1A3 variant; product improved with AA rear sight. MG 3E: MG 3 variant; reduced weight model (roughly 1.3 kg lighter), entered into late 1970s NATO small arms trials. MG 3A1: MG 3 variant; for fixed mount armor use.



Category	<i>Light Machine Guns</i>
Operating system	recoil-operated, roller locked
Cartridge	
Feeding	belt fed

The following ammunition can be used by the **MG 3 / MG 42**:

Mossberg 500

The Mossberg 500 is a series of pump-action shotguns manufactured by the American company O.F. Mossberg & Sons. These shotguns have been produced since 1960 and



with a series of different models including the numbers 505, 510, 535, and 590. The Mossberg 500 shotgun series is designed to be used under harsh field conditions, as it is easy to clean and to maintain.

Category	<i>Rifles & Carbines</i>
Operating system	manual, slide-action
Cartridge	12-gauge
Length	1022 mm
Feeding	underbarrel tubular magazine

The following ammunition can be used by the **Mossberg 500**:

12-gauge

Bullet diameter	18.53 mm
Case length	-
Overall length	-

NO IMAGE

MP UZI

The UZI and the Czechoslovakian series Sa 23 to Sa 26 were the first weapons to use a telescoping bolt design, in which the bolt wraps around the breech end of the barrel. This allows the barrel to be moved far back into the receiver and the magazine to be housed in the pistol grip, allowing for a heavier, slower-firing bolt in a shorter, better-balanced weapon. The pistol grip is fitted with a grip safety, making it difficult to fire accidentally. It was built in Belgium under license for export to Germany and Iran. Croatia manufactured unlicensed copies of the Uzi and Micro-Uzi called the ERO and Mini ERO respectively. Mini- and Micro-Uzi submachine guns are produced either in open-bolt or closed-bolt versions.



Category	<i>Submachine Guns</i>
Operating system	Blowback-operated, fired from open bolt
Cartridge	9mm Parabellum (9 x 19mm)
Length	470 mm
Feeding	Box magazine

The following ammunition can be used by the **MP UZI**:

9mm Parabellum (9 x 19mm)

Bullet diameter	9 mm
Case length	19.15 mm
Overall length	29.69 mm



Remington 870P

The Remington Model 870 pump-action shotgun is available in 11 versions with various barrel lengths, furniture alternatives and magazine capacities. The first model entered into production in 1951. Current models are still being produced today, adding to the more than 10,000,000 estimated units already produced. The Model 870P is the police model with its receiver made of steel. This model can also carry four extra rounds of ammunition. The Remington 870 series is in service with numerous military and police forces worldwide.



Category	<i>Rifles & Carbines</i>
Operating system	manual, slide-action
Cartridge	12-gauge
Length	971 mm
Feeding	underbarrel tubular magazine

The following ammunition can be used by the **Remington 870P**:

12-gauge

Bullet diameter	18.53 mm
Case length	-
Overall length	-



SIG SG540

The Swiss SIG SG540 was designed as a potential replacement for the SG510. It was produced between 1977 and 2002 in Switzerland and remains in production in Chile only. While the SG540 and the SG 543 models are chambered for the 6.56 x 45 mm caliber, the SG542 uses 7.62 x 51 mm NATO cartridges.



Category	<i>Assault Rifles</i>
Operating system	gas, selective-fire
Cartridge	5.56 x 45mm / .223 Remington
Length	950 mm
Feeding	detachable box magazine

The following ammunition can be used by the **SIG SG540**:

5.56 x 45mm / .223 Remington

Bullet diameter	5.7 mm
Case length	44.7 mm
Overall length	57.4 mm



Steyr AUG

The rifle is fully ambidextrous. It can be configured for use by left-handed shooters by simply changing the bolt for a left-handed one with the extractor and ejector on opposite sides, and moving a blanking cap from the left ejection opening to the right. The housing of the AUG rifles, integral with the pistol handle and trigger guard, is made from the high impact-resistant polymer, and is usually of green or black color. The Australian Army's modified version of the Steyr AUG A1 is called F88 Austeyr. It is also used by the Falklands Defense Forces.



Category	<i>Assault Rifles</i>
Operating system	Gas operated, rotating bolt

Cartridge	5.56 x 45mm / .223 Remington 9mm Parabellum (9 x 19mm)
Length	790 mm
Feeding	Box magazine

The following ammunition can be used by the **Steyr AUG**:

5.56 x 45mm / .223 Remington

Bullet diameter	5.7 mm
Case length	44.7 mm
Overall length	57.4 mm



9mm Parabellum (9 x 19mm)

Bullet diameter	9 mm
Case length	19.15 mm
Overall length	29.69 mm



Strela (SA-7 / SA-14)

The missile launcher system consists of the green missile launch tube containing the missile, a grip stock and a cylindrical thermal battery. The launch tube is reloadable at depot, but missile rounds are delivered to fire units in their launch tubes. The device can be reloaded up to five times. The Strela and its variants have been widely used in nearly every regional conflict since 1968.



Category	<i>Portable Launcher of Anti-aircraft Missile Systems</i>
Operating system	MANPAD
Cartridge	
Feeding	front-loaded

The following ammunition can be used by the **Strela (SA-7 / SA-14)**:

Tagging of Sources

We believe that our Guide should be as transparent as possible without endangering the confidentiality of our sources. Rather than name the exact source for each unit of data, we have created tags so that users can at least know whether the data comes from a primary or secondary source, and by which medium it can or has been found. All incoming data is validated and then tagged by the project team at BICC before it enters our database.

Sources are tagged according to the following criteria:

1. Primary Sources:

These are presentations of facts. They are proof of an SALW event (e.g. a transfer, sighting, misuse, etc.) because the source was created at the time of the event itself. Primary sources are usually original documents such as transfer authorizations, firearms legislation, or academic journals presenting results of a study on SALW holdings in a particular country, for example. However, they can also be information offered by a person with direct knowledge of an SALW event or who has documented an SALW event at the time that it happened.

2. Secondary Sources:

These are interpretations or evaluation of facts. Secondary sources contain commentary and analysis of SALW events that are documented in primary sources.

Sources are also tagged according to the dominant medium of delivery:

A. Written - the source is based on written words.

B. Oral - the source is based on spoken words.

C. Visual - the source is based on seen events or optical images.

These criteria make our tags two-dimensional. While the process of classifying sources is a primarily subjective one, the project team at BICC has developed the following table to serve as an example of possible sources within each category.

Table: Examples of sources on SALW distribution

	Primary	Secondary

<p>Written</p>	<ul style="list-style-type: none"> • Fact books • Weapons Transfer authorizations • End-user certificates • Transcripts of interviews, legal proceedings, speeches/ presentations, meetings, conferences or symposia • Newspaper articles • Written correspondence (e.g. letters, emails, text messages, etc.) • Blogs • Peer-reviewed journal articles • Treaties, constitution, laws • Records of organizations (e.g. annual reports) • Surveys, questionnaires <p>Etc...</p>	<ul style="list-style-type: none"> • Wikipedia • Literature reviews • Training or safety manuals on gun control, ammunition, physical stockpile security management) • Minutes of meetings, conferences, symposia • Indexes (e.g. Global Militarization Index) • Newspaper articles <p>Etc.</p>
<p>Oral</p>	<ul style="list-style-type: none"> • Interviews with experts, including radio or telephone • Legal proceedings • Speeches or interventions by experts or national representatives in government or international meetings <p>Etc ...</p>	<ul style="list-style-type: none"> • Speeches, panel presentations, etc. on data provided by experts <p>Etc...</p>
<p>Visual</p>	<ul style="list-style-type: none"> • Artifacts (e.g. the weapons themselves, ammunition) • Photographs of weapons, ammunition, etc. • Videos (e.g. YouTube, those recorded by mobile phone) • Television documentaries, news reports <p>Etc ...</p>	<ul style="list-style-type: none"> • PowerPoint presentations on results found by experts <p>Etc...</p>

Table: Example tags

Source (sample)	Type of source	Medium of delivery
IHS Jane's Weapons Infantry (2015-2016)	primary	written
Panel discussion of weapons use of non-state armed groups	secondary	oral
Documentary on paramilitaries in Colombia	primary	visual

About the Guide

The Interactive Guide on **Small Arms and Light Weapons** is an open access tool, designed to build knowledge on how to identify different types, makes and models of commonly used SALW in organized violence; to collect data on the global and country-specific spread of these SALW; and to describe some of their visual and technical specifications.

The guide is not an exhaustive list of all SALW that are used around the world.

Global SALW control relies on, among other things, data and knowledge of the weapons themselves. Our aim is that the Guide will be used to support national reporting duties on SALW holdings; facilitate and ameliorate the collection of data on SALW; and increase general knowledge of global distribution of SALW.

The interactive Guide was developed by **BICC** in close cooperation with the **Bundeswehr Verification Center** (BwVC), and with the generous support of the *Federal Foreign Office, Germany*.

Contact

**Internationales Konversionszentrum Bonn -
Bonn International Center for Conversion (BICC) GmbH**

Lars Wirkus
Head of Data & Geomatics
Pfarrer-Byns-Str. 1
53121 Bonn

Germany

E-Mail: wirkus@bicc.de

Internet: www.bicc.de

**Zentrum für Verifikationsaufgaben der Bundeswehr (ZVBw) - Bundeswehr
Verification Center (BwVC)**

Global Arms- and Proliferation Control Division

Captain Laurentius Wedeniwski

Selfkant-Kaserne

Rue de Quimperle 100

52511 Geilenkirchen

E-Mail: LaurentiusWedeniwski@bundeswehr.org

Overall project coordination

Lars Wirkus

Head of Data & Geomatics

Bonn International Center for Conversion (BICC)

Responsible for all content (including photos):

Zentrum für Verifikationsaufgaben der Bundeswehr (ZVBw) - Bundeswehr Verification Center.

Captain Laurentius Wedeniwski: Small Arms and Light Weapons Guide (2016).

Responsible for design, editorial and technical implementation:

Internationales Konversionszentrum Bonn - Bonn International Center for Conversion (BICC) GmbH.

Technical management: Lars Wirkus

Programming: Rolf Alberth